

					
Date début : 13/10/2020		Machine : FL40.16		Profondeur : 0.00 - 15.00 m	
				X : -1.1637076	
				Y : 44.3951558	

1/100

Forage : SP_1

EXGTE B3.22.7/GTE

Cote (m)	Profondeur (m)	Lithologie	Niveau d'eau (m)	Outil	Fluide	Tubage	Equipement forage	Profondeur (m)	EM (MPa)	pl-p0 (MPa)	pl-p0 (MPa)	EM / (pl-p0)
-0.70	0	Sables gris						0				
	1	0.70 m						1	0.1		0.02	< 2.0
	2							2	0.9		0.05	< 18.4
	3		1.36 m					3	16.4	1.60	0.68	10.2
	4		22/10/2020 Niveau stabilisé					4	9.5	1.79	1.26	5.3
	5							5	6.6	1.39	0.96	4.7
	6							6				
	7							7	13.2	1.49	1.11	8.8
	8	Sables beiges		Taillant rotation 64mm	Bentonite	Roto-percussion diam 68-83 mm	Piézomètre PVC Ø41-48 mm - Longueur totale : 12 m Crépiné de 3 à 12 m - Avec chaussette	8	9.3	1.33	1.05	7.0
	9							9				
	10							10	13.3	1.45	0.71	9.2
	11							11				
	12					12.00 m		12	19.5	2.25	1.66	8.7
	13							13	13.2	1.85	1.47	7.2
	14							14				
-15.00	15	15.00 m		15.00 m	15.00 m	15.00 m		15	16.9	1.85	1.00	9.1

Fondasol - EARS - ITTP - A - Version 10-2018 page 60